

UNITED STATES PATENT APPLICATION

for

**METHOD AND APPARATUS FOR TRANSMITTING DATA OVER
A NETWORK USING A DOCKING DEVICE**

Applicants:

John Higginson
Deane Gardner
Andreas Bibl

prepared by:

BLAKELY, SOKOLOFF, TAYLOR & ZAFMAN
12400 Wilshire Boulevard
Los Angeles, CA 90026-1026
(408) 720-8598**EXPRESS MAIL CERTIFICATE OF MAILING**"Express Mail" mailing label number EL672750708USDate of Deposit April 2, 2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Commissioner of Patents and Trademarks, Washington, D.C. 20231.

Michelle Begay

(Typed or printed name of person mailing paper or fee)

Michelle Begay
(Signature of person mailing paper or fee)

**METHOD AND APPARATUS FOR TRANSMITTING DATA OVER A
NETWORK USING A DOCKING DEVICE**

BACKGROUND OF THE INVENTION

5 This application is a continuation-in-part of application Ser. No. 09/476,142,
filed January 3, 2000.

1. Field of the Invention

The present invention relates to data communication. More particularly, the
present invention relates to transmitting data over a network using a docking device.

10 **2. Background Information**

Physical fitness is known to benefit people in many different areas, including
improved flexibility and range of motion, increased muscular strength and
cardiovascular fitness, body fat loss and increased stamina. Physical exercise helps
maintain good health, increases energy, reduces stress and improves physical
15 appearance. However, in order to gain the benefits of regular physical exercise, an
exercise program needs to be carefully designed and correctly followed. It is
desirable that a person engaged in a physical training program is guided by a
professional fitness instructor or an athletic trainer. People with health problems
may need to exercise under close supervision of a physician. A person who seeks to
20 lose weight may need to get a recommendation on how to coordinate physical
exercise and dieting.

In today's busy world, it is unlikely that many people can fully benefit from physical exercise unless the professional advice is readily available to them.

However, the professional advice is only as good as the information provided to the professional by the person engaged in physical exercise. Conventional devices are

5 known for obtaining this information via monitoring. Several prior art fitness

monitoring devices are designed to provide the users with quick access to

information concerning their exercise level. For example, U.S. Patent No. 5,810,722

describes a device for measuring heartbeat rate. An athlete or a person engaged in fitness training may wear the device on the chest or the wrist. The device measures

10 the heartbeat rate based on skin contact and allows the user to read the result from a display provided in the casing of the device. U.S. Patent No. 5,891,042 describes a

fitness monitoring device which includes an electronic pedometer integrated

together with a wireless heart rate monitor. The device may be secured to the user's belt or waist band. The device receives electrical signals from a telemetric

15 transmitter unit arranged on the user's skin adjacent to his heart and calculates the heart rate. The device is also configured to detect the user's body motion at each step for performing step counting. The user can read the results from a display provided

in the casing of the device. The display includes an alpha/numeric display portion and a heart rate monitoring icon. These prior art devices, however, merely allow the

20 users to see the physiological information concerning their exercise level. They do not provide any processed feedback or professional guidance to the users. In

addition, these devices can be cumbersome to wear and they force the users to monitor their own activity, thereby interfering with their focus on physical exercise.

The prior art also includes fitness monitoring systems that allow some interaction between a user and a professional trainer. U.S. Patent No. 5,598,849
5 describes a fitness monitoring system which includes a user monitor and a fitness system workstation. The monitor is mounted on a user's wrist and operates in conjunction with a heartbeat monitor mounted on a user's chest. The fitness system workstation is a local area network which includes a master computer and an interactive voice response computer. A personal trainer examines the user in a
10 fitness center and obtains the physiological parameters for the user. Based upon these parameters, the master computer determines a suitable exercise regimen for the user. The personal trainer manually programs the user monitor and instructs the client in its use. During physical exercise, the user monitor indicates to the user whether his heart rate is above or below predetermined limits. The user can
15 download data to the fitness system workstation by telephoning the fitness system workstation, holding the pulse code output against the telephone and actuate an appropriate push button on the keyboard to transfer data. At intervals, the fitness system workstation generates detailed reports relating to the user's performance. A personal trainer analyzes these reports and places a voice message for the user in the
20 master computer. The voice message may be delivered to the user when the user telephones the fitness system workstation to download further exercise data.

Although the above prior art system provides some interactive monitoring of a user's exercise activity, this monitoring is very limited. In addition, the use of the system is cumbersome and requires visits to the fitness center. Furthermore, the feedback provided by the system is narrow and may not satisfy the user's needs with
5 respect to physical exercise.

Therefore, what is required is an interactive fitness monitoring system which will make a wide variety of health and fitness information readily available to users and will effectively assist the users in their fitness activity.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209

SUMMARY OF THE INVENTION

A method and system for transmitting data over a network are described.

According to one aspect of the present invention, the system comprises a cradle to transmit data to a network server and an electronic device coupled to the cradle. The
5 electronic device includes a sensor to trigger a data connection between the electronic device and the cradle. The electronic device also includes a data transmitter to download the data to the cradle.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and may be better understood by referring to the following description in conjunction with the accompanying drawings, in which like references indicate similar elements and in
5 which:

Figure 1 is a block diagram of one embodiment for a network architecture;

Figure 2 is a block diagram of one embodiment for an architecture of a computer system;

Figure 3 is a flow diagram of one embodiment for managing data of subscribers via a network;
10

Figure 4 is a block diagram of one embodiment for a personal data capture device;

Figure 5 is a block diagram of another embodiment for a personal data capture device;

Figure 6 is a flow diagram of one embodiment for monitoring data of subscribers using a personal data capture device;
15

Figure 7 is a flow diagram of one embodiment for posting personal data of a subscriber on a web site;

Figures 8A-8C illustrate downloading personal data from a personal data capture device to a cradle; and
20

Figure 9 is a flow diagram of one embodiment of a method for transmitting data over a network using a docking device.

**DETAILED DESCRIPTION OF AN EMBODIMENT OF THE PRESENT
INVENTION**

A method and system for transmitting data over a network using a docking device are described. In the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be apparent to one skilled in the art that the present invention may be practiced without these specific details. In some instances, well-known structures and devices are shown in block diagram form, rather than in detail, in order to avoid obscuring the present invention.

Some portions of the detailed descriptions that follow are presented in terms of algorithms and symbolic representations of operations on data bits within a computer memory. These algorithmic descriptions and representations are the means used by those skilled in the data processing arts to most effectively convey the substance of their work to others skilled in the art. An algorithm is here, and generally, conceived to be a self-consistent sequence of processing blocks leading to a desired result. The processing blocks are those requiring physical manipulations of physical quantities. Usually, though not necessarily, these quantities take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It has proven convenient at times, principally for reasons of common usage, to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like.

It should be borne in mind, however, that all of these and similar terms are to be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities. Unless specifically stated otherwise as apparent from the following discussion, it is appreciated that throughout the description, discussions utilizing terms such as "processing" or "computing" or "calculating" or "determining" or "displaying" or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

The present invention also relates to apparatus for performing the operations herein. This apparatus may be specially constructed for the required purposes, or it may comprise a general purpose computer selectively activated or reconfigured by a computer program stored in the computer. Such a computer program may be stored in a computer readable storage medium, such as, but is not limited to, any type of disk including floppy disks, optical disks, CD-ROMs, and magnetic-optical disks, read-only memories (ROMs), random access memories (RAMs), EPROMs, EEPROMs, magnetic or optical cards, or any type of media suitable for storing electronic instructions, and each coupled to a computer system bus.

The algorithms and displays presented herein are not inherently related to any particular computer or other apparatus. Various general purpose systems may

be used with programs in accordance with the teachings herein, or it may prove convenient to construct more specialized apparatus to perform the required method steps. The required structure for a variety of these systems will appear from the description below. In addition, the present invention is not described with reference
5 to any particular programming language. It will be appreciated that a variety of programming languages may be used to implement the teachings of the invention as described herein.

Referring now to **Figure 1**, a block diagram of one embodiment for a network architecture is illustrated. In this embodiment, portable sports appliance (PSA) 110 is
10 coupled to cradle 120. PSA 110 may be used to monitor and store physical and biometrical parameters of its user. In this embodiment, PSA 110 is a portable device. However, it will be recognized by one of ordinary skill in the art that a stationary device or a device included in some other device or equipment may be used with this invention without loss of generality. PSA 100 may be used by any person. For
15 example, PSA 100 may be used by a person engaged in fitness activity, a professional athlete during exercise, or an employee wishing to know how his stress level changes during the day. The operation of PSA 110 and its functions will be described in more details below.

Cradle 120 is used to upload data from personal data capture device 100 to
20 network 150. In one embodiment, cradle 120 may resemble a support element for a telephone receiver or handset. Cradle 120 may include a modem to transmit data

over telephone lines and may be configured to provide two-way connection to wide area network 150.

In one embodiment, placing personal data capture device 110 in cradle 120 may trigger an automatic dialing of a telephone number of server 160. When the telephone line is free, data from personal data capture device 110 may then be transmitted to server 160 via cradle 120 over wide area network 150. In one embodiment, the data is transmitted to cradle 120 via a two-directional infrared communication link between personal data capture device 110 and cradle 120. Alternatively, the data may be downloaded from personal data capture device 100 to cradle 120 using any data communication technique known in the art. One embodiment of downloading data to cradle 120 is described in greater detail below in conjunctions with **Figures 8A-8C**.

In another embodiment, the data may be transmitted from personal data capture device to server 160 using a wireless transmitter. That is, cradle 120 is not used, and the data is transmitted over a wireless carrier. It should be understood by one of ordinary skill in the art that various ways of transmitting data from PSA 110 to server 160, other than those described above, may be used with this invention without loss of generality.

Cradle 120 may be used with more than one PSA 110. For example, if each family member has his or her own PSA 100, cradle 120 may be shared by all family members. Personal data of each family member is then uploaded to server 160 at various points of time. Server 160 may receive personal data from numerous PSA

users. This personal data may then be processed by third parties that may provide feedback information to those PSA users who subscribe for this service.

In one embodiment, server 160 is coupled to wide area network 150. Wide area network 150 may include, for example, the Internet, America On-Line™, CompuServe™, Microsoft Network™, or Prodigy™. In addition, wide area network 150 may include, for example, conventional network backbones, long-haul telephone lines, Internet service providers, or various levels of network routers. Using conventional network protocols, server 160 may communicate through wide area network 150 to a plurality of clients.

In one embodiment, server communicates to clients 130 and 170. Clients 130 and 170 represent any device that may enable user's access to data. For simplicity, **Figure 1** shows only two clients, client 130 and client 170, that can communicate to server 160. However, it will be recognized by one of ordinary skill in the art that server 160 may communicate to a various number of clients and that a wide variety of client devices may be used with this invention without loss of generality. Such devices may include, for example, a conventional computer system, a network computer or thin client device (e.g., WebTV Networks™ Internet terminal or Oracle™ NC), a laptop or palm-top computing device (e.g., Palm Pilot™), a digital consumer device (e.g., a digital TV, a digital camcorder, or a "kitchen" computer"), etc. In one embodiment, clients 130 and 170 may have a Graphical User Interface (GUI) to allow users to access data. A GUI is a graphics-based user interface that incorporates icons,

pull-down menus and a mouse. GUIs may include, for example, Microsoft Windows, Apple Macintosh, UNIX Motif, or UNIX OPENLOOK.

Clients 130 and 170 may be connected to server 160 in various ways. In one embodiment, clients 130 and 170 may be connected to server 160 through wide area
5 network 150. Client 170 may represent client devices of third parties, e.g., health and fitness specialists, who access personal data of subscribers on server 160 via wide area network 150 to generate feedback information to subscribers. Client 130 may represent client devices of subscribers who access the generated feedback information via wide area network 150. In this embodiment, client 130 is connected
10 to cradle 120 which provides two-way connection with wide area network 150. However, it will be understood by one of ordinary skill in the art that client 130 does not need to be connected to cradle 120. Instead, client 130 may use the same connection means as client 170.

In an alternate embodiment (not shown in **Figure 1**), a client, such as client 130
15 or client 170, may be directly connected to server 160 or through a modem in a conventional way. When connected to wide area network 150, clients 130 and 170 may be connected directly to wide-area network 150 through direct or dial up telephone or other network transmission line. Alternatively, clients 130 and 170 may be connected to wide-area network 150 using a modem pool. A conventional
20 modem pool may allow a plurality of clients to connect with a smaller set of modems in modem pool for connection to wide-area network 150. In yet another network typology, wide-area network 150 may be connected to a gateway computer, which

may be used to route data to clients through a local area network. In this manner, clients can communicate with each other through a local area network (LAN) or with server 160 through a gateway and wide-area network 150. Alternatively, LAN may be directly connected to server 160 and clients may be connected through LAN. For example, subscribers' personal data may be processed by a company employing fitness instructors, athletic trainers, physicians and other health and fitness specialists. Such a company may use LAN topology for providing internal communication between its employees. LAN may then be connected to server 160 through wide area network 150 for allowing communication between subscribers and health and fitness specialists.

Using one of a variety of network connection means, server computer 160 may communicate with clients 150 using conventional means. In one embodiment, a server computer 160 may operate as a web server if the World-Wide Web (WWW) portion of the Internet is used for wide area network 150. Using the HTTP protocol and the HTML coding language across a network, web server 160 may communicate across the World-Wide Web with clients 130 and 170. In this configuration, clients 130 and 170 may use a client application program known as a web browser such as the Netscape™ Navigator™ published by Netscape Corporation of Mountain View, CA, the Internet Explorer™ published by Microsoft Corporation of Redmond, Washington, the user interface of America On-Line™, or the web browser or HTML translator of any other conventional supplier. Using such conventional browsers and the World-Wide Web, clients 130 and 170 may access graphical and textual data or

video, audio, or tactile data provided by web server 160. Conventional means exist by which clients 130 and 170 may supply information to web server 160 through the World-Wide Web 150 and the web server 160 may return processed data to clients 130 and 170.

5 Having briefly described one embodiment of the network environment in which the present invention operates, **Figure 2** illustrates an example of a computer system 200 illustrating an exemplary client 130 or 170, or server 160 computer system in which the features of the present invention may be implemented. Referring to **Figure 2**, computer system 200 is comprised of a bus or other communications means
10 201 for communicating information, and a processing means such as processor 202 coupled with bus 201 for processing information. Computer system 200 further comprises a random access memory (RAM) or other dynamic storage device 204 (commonly referred to as main memory), coupled to bus 201 for storing information and instructions to be executed by processor 202. Main memory 204 also may be
15 used for storing temporary variables or other intermediate information during execution of instructions by processor 202. Computer system 200 also comprises a read only memory (ROM) and /or other static storage device 206 coupled to bus 201 for storing static information and instructions for processor 202.

 An optional data storage device 207 such as a magnetic disk or optical disk
20 and its corresponding drive may also be coupled to computer system 200 for storing information and instructions. Computer system 200 can also be coupled via bus 201 to a display device 221, such as a cathode ray tube (CRT) or a liquid crystal display

(LCD), for displaying information to a computer user. For example, graphical or textual information may be presented to the user on display device 221. Typically, an alphanumeric input device 222, including alphanumeric and other keys is coupled to bus 201 for communicating information and/or command selections to processor

5 202. Another type of user input device is cursor control device 223, such as a conventional mouse, touch mouse, trackball, or other type of cursor direction keys for communicating direction information and command selection to processor 202 and for controlling cursor movement on display 221. A fully-loaded computer may optionally include video, camera, speakers, sound card, and many other

10 conventional options.

Alternatively, clients 130 and 170 can be implemented as any device described above. Such a device does not necessarily include all of the elements and features of the above-described exemplary computer system; however, the functionality of the present invention may nevertheless be implemented with such devices.

15 A communication device 225 is also coupled to bus 201 for accessing remote computers or servers, such as web server 160, or other servers via the Internet, for example. The communication device 225 may include a modem, a network interface card, or other well known interface devices, such as those used for interfacing with Ethernet, Token-ring, or other types of networks. In any event, in this manner, the

20 computer system 200 may be coupled to a number of servers 160 via a network infrastructure such as the infrastructure illustrated in **Figure 1** and described above.

Figures 8A-8C illustrate downloading data from an electronic device such as a personal data capture device 110 to a cradle, according to one embodiment of the present invention. Referring to **Figure 8A**, an exemplary cradle 102 is shown that may be used to hold an electronic device (e.g., an electronic device 810 shown in **Figure 8B**), to receive data from the electronic device, and to transfer this data to a network server such as web server 160. Cradle 802 includes a data receiver 804. Electronic device 810 includes a data transmitter 814 and a sensor 812. In one embodiment, an infrared connection is used to download data from electronic device 810 to cradle 802. In this embodiment, the data receiver 804 in cradle 802 represents an infrared receiver, and cradle 802 includes a magnet 806. Accordingly, the data transmitter 814 in the electronic device 810 represents an infrared transmitter and sensor 812 represents a magnetic read switch. It should be noted that cradle 802 and electronic device 810 may have various shapes and designs, and may include a variety of elements other than those described above.

In one embodiment illustrated in **Figure 8C**, when electronic device 810 is placed into cradle 802, magnetic read switch 812 detects magnet 806 of cradle 802 and sends a signal to a microprocessor of electronic device 810. The microprocessor then activates infrared transmitter 814 which begins downloading data from electronic device 810 to cradle 802 using infrared receiver 804. When the downloading is completed, the infrared connection between electronic device 810 and cradle 802 is terminated. In one embodiment, the microprocessor of electronic device 810 terminates the infrared connection upon receiving a signal from infrared transmitter

814 indicating that the downloading has been completed. Alternatively, the microprocessor establishes the infrared connection for a predetermined period of time and terminates the infrared connection when this period of time expires.

Figure 9 is a flow diagram of a method 900 for transmitting data over a network using a docking device such as cradle 802. Method 900 begins with activating a sensor (e.g., magnetic read switch, a mechanical switch, etc.) in an electronic device such as a personal data capture device (processing block 904). In one embodiment, the sensor is activated when the electronic device is placed into the cradle. For example, a magnet or a mechanical means may be used to activate the sensor.

In response to the activation of the sensor, a data connection is established between the electronic device and the cradle (processing block 906). In one embodiment, the data connection is infrared.

At processing block 908, data captured in the electronic device is downloaded to the cradle. In one embodiment, the electronic device captures personal data of the user of the electronic device. The user may also be a subscriber of a service provided by a network server as will be described in greater detail below.

When the downloading is completed, the data connection is terminated. In one embodiment, the connection is terminated when a data transmitter of the electronic device sends a signal indicating that the downloading has completed. In an alternative embodiment, the data connection is terminated when a predefined download time period has expired. In either embodiment, the data connection is

established only for a limited period of time to minimize power consumption of the electronic device and cradle.

Afterwards, at processing block 910, the data is transmitted from the cradle to a network server. In some embodiments, the data is transmitted using a modem. In
5 other embodiments, the data may transmitted from the cradle to the network server via a wireless carrier or using any other data communication technique known in the art.

Figure 3 is a flow diagram of one embodiment for managing data of subscribers via a network. At processing block 304, personal data of a subscriber is
10 captured in a personal data capture device. The personal data includes physical and biometrical parameters of the subscriber. These parameters may be measured at any time and during any activity of the subscriber, including, for example, physical exercise, work related activities, or quiet time at home. The process of measuring the
15 parameters and capturing them in the personal data capture device will be described in more detail below.

At processing block 304, the personal data is transmitted from the personal data capture device to a network server. In one embodiment, the personal data may be transmitted using a cradle. That is, the personal data capture device is placed in the cradle which triggers an automatic dialing of a telephone number of the server.
20 When the telephone line is free, data from the personal data capture device may be transmitted to the web server through a wide area network. The transmitted data may include a unique identifier associated with the data capture device.

Alternatively, the cradle may not be used, and the personal data may be transmitted to the web server using a wireless transmitter via a wireless carrier.

The server stores personal data of subscribers. In one embodiment, each subscriber is required to have an account registered at the web server in order to
5 receive services provided by the web server. The account may need to be created before personal data is first transmitted to the web server. In alternate embodiments, the account may be created when the personal data capture device is purchased or at the time of first transmission of personal data to the web server.

At processing block 308, the personal data is analyzed to generate feedback
10 information. In one embodiment, the personal data on the web server may be accessed by a third party. The third party may include, for example, a fitness instructor, an athletic trainer, a diet or nutrition specialist, a physician, or any other fitness or health specialist. One or more specialists may have access to the personal data of the subscriber depending on the subscriber's needs and subscribed services.
15 Every specialist involved in the subscribed services may create feedback information based on the personal data of the subscriber.

At processing block 310, the feedback information is presented to the subscriber over a wide area network. In one embodiment, the subscriber accesses the feedback information upon entering a password. The password may be associated
20 with the subscriber's account. Alternatively, the subscriber may need to enter a code associated with the personal data capture device or any other unique information allowing to prevent access to the subscriber's personal data by outsiders. It will be

understood by one of ordinary skill in the art that various other ways of maintaining confidentiality of the subscriber's personal data may be used with the present invention without loss of generality.

In one embodiment, the feedback information is posted on a private web site of the subscriber. Alternatively, the subscriber may access the feedback information on a particular web site known to all subscribers (e.g., /www.sportbrain.com/) upon entering a password or a certain unique code. In addition to the feedback information, the personal data may be presented to the subscriber in numerous forms. The numerous forms may include, for example, various graphs, tables, map overlays, progressive charts, and comparisons with data of other subscribers.

In one embodiment, the personal data capture device may be configured from the web site by the subscriber. Alternatively, the personal data capture device may be configured by a health or fitness specialist over the wide area network. For example, a fitness instructor may decide to reconfigure the personal data capture device according to a new version of the exercise program that the instructor designed for the subscriber based on the recent personal data of the subscriber. In yet another embodiment, both the subscriber and the instructor may have the ability to reconfigure the personal data capture device over the network.

The personal data capture device will now be described in more detail. **Figure 4** is a block diagram of one embodiment for a personal data capture device. Referring to Figure 4, personal data capture device 400 includes microprocessor 460 which is coupled to memory 480, software program 482 and electronics 484. In one

embodiment, personal data capture device 400 is a portable device. In this embodiment, personal data capture device 400 may be clipped to the user's waist band, or may be secured to the user in other ways such as via a wrist watch-type arrangement or by simply being held by the user. In alternate embodiments,

5 personal data capture device 400 may be a stationary device or a device included in some other device or equipment.

In one embodiment, personal data capture device 400 includes a global positioning system (GPS) signal receiver 430 which receives GPS signals 410. GPS signals 410 may include three-dimensional positional information and velocity of the

10 user when the user is walking or running, or is engaged in some other relevant activity. Personal data capture device 400 may also include a motion sensor 450 which may improve the accuracy of the above information or substitute it when GPS signal 410 is interrupted. In addition, personal data capture device 400 may include heart rate receiver 430 which receives heart beat rate from wireless heart rate

15 transmitter 420. Various other sources may provide signals to personal data capture device 400. Personal parameter transmitter 405 represents a wide variety of signals that may be received by various personal parameter receivers 425 included in personal data capture device 400. For example, a bathroom weight scale may have a transmitter built in it to automatically transmit signals with weight data to personal

20 data capture device 400. A blood pressure meter, a glucose meter, exercise equipment such as treadmills and stationary bikes, or any other device or equipment can transmit data to personal data capturing device 400 which will receive it using a

corresponding personal parameter receiver 425. In one embodiment, heart rate receiver 440 is personal parameter receiver 425. It will be understood by one of ordinary skill in the art that all of the receivers described above or any combination of them may be included in personal data capture device 400 without loss of
5 generality.

Upon receiving a signal, any of the receivers 425 through 450 outputs data to microprocessor 460. Microprocessor 460 stores this data in memory 480. In one embodiment, personal data capture device may include electronic beeper 470 for providing audio signals related to the personal data. For example, when personal data capture device 400 is configured over the network as described above, electronic beeper 470 can be set to signal low and high heart rate target limits, low and high pace limits, low and high weight limits, etc. Alternatively, or in addition to electronic beeper 470, personal data capture device 400 may include digital audio 472 to provide more detailed feedback. Digital audio 472 may be configured to provide various real time information (e.g., distance average speed) related to personal parameters transmitted to personal data capture device 400. Personal data capture device 400 may also include digital audio player such as MP3 player 474 to play digital recordings. In one embodiment, the real time information generated by digital audio 472 and/or digital recordings played by MP3 player may be
10
15
20 communicated to the user by earphone 476 coupled to digital audio 472 and/or MP3 player 474. It will be understood by one of ordinary skill in the art that any combination of personal data receivers 425 through 450 and audio signal generators

470 through 476 may be used with personal data capture device 400 without loss of generality.

In one embodiment, microprocessor 460 is coupled to modem 490 which is contained in a cradle. Modem 490 provides a direct two-way connection to web
5 server 160 and subscriber's web site 492 over a wide area network. In this embodiment, when personal data capture device 400 is placed in the cradle, modem 490 automatically dials a phone number of web server 160. When the phone line is free, software 482 causes microprocessor 460 to upload subscriber's personal data from memory 480 to web server 160. Alternatively, personal data capture device
10 may include a wireless transmitter (not shown) which may be used by microprocessor 460 to transmit the subscriber's personal data from memory 480 to web server 160 via a wireless carrier.

In one embodiment, the subscriber's personal data may be posted on subscriber's web site 492. Alternatively, web site 492 may be a company web site
15 which can be accessed by all subscribers. GUI 494 is coupled to web site 492 to provide the user with a convenient way to view the data.

In one embodiment, the user may be provided with an option of adding new features to personal data capture device 400 over the wide area network. For example, the user may be notified of availability of a new or improved version for
20 personal data capture device 400. The user may then be allowed to download the new or improved version directly over the Internet.

Figure 5 is a block diagram of another embodiment for a personal data capture device. Referring to Figure 5, personal data capture device 500 may include the same features and functionality as personal data capture device 400. In one embodiment, personal data capture device 500 includes all data receivers 425 through 450 and all audio signal generators 470 through 476. In alternate embodiments, personal data capture device 500 may include any combination of receivers 425 – 450 and audio signal generators 470 – 476.

In one embodiment, panic button 486 is coupled to microprocessor 460. In this embodiment, software 482 analyzes personal data in memory 480. If the personal data includes a parameter that is below or exceeds a certain panic parameter (e.g., heart rate is too low or too high), software 482 may cause microprocessor 460 to invoke panic button 486. Panic button 486 may then produce a panic signal to a satellite page service or a cellular service 422. In one embodiment, the panic parameters may be set or updated from the user's web site 492 and transferred to memory 480 over the wide area network. In alternate embodiments, the panic parameters may be set or updated by health or fitness specialists in web server 160 or programmed during the manufacture of personal data capture device 500.

In one embodiment, GPS receiver 496 is coupled to modem 490. GPS receiver 496 receives signals directly from GPS 410 to provide differential correction of GPS signals. Alternatively, differential correction of GPS signals may be done from a personal web site of a subscriber or from a company web site.

Figure 6 is a flow diagram of one embodiment for monitoring data of subscribers using a personal data capture device. Referring to Figure 6, at processing block 604, personal data is received by personal parameter receivers. As described above, the personal data may be received from one or more sources. Personal parameter receivers may include, for example, a GPS signal receiver, a heart rate receiver, a motion sensor, a weight data receiver, a blood pressure receiver, a glucose measurement receiver, or an exercise data receiver.

At processing block 606, the personal data is stored in the personal data capture device. The personal parameter receivers output the personal data to microprocessor 460 which stores the personal data in memory 480 of the personal data capture device. The personal data may include a timestamp and information identifying a source of a personal parameter. In one embodiment, when the personal data includes certain parameters, an audio signal may be produced by electronic beeper 470. In addition, certain real time information may be communicated to the user by digital audio 472 and earphone 476 based upon the personal data.

Alternatively or in addition to the above audio signals, when the personal data includes a panic parameter, a panic signal may be generated to a satellite page service or a cellular service.

At processing block 608, the personal data is transmitted from memory 480 to the web server via the wide area network. In one embodiment, the personal data may be transmitted over a phone line using cradle 120 which may have a direct two-way connection to the Internet. Alternatively, the personal data may be transmitted

from the personal data capture device to the web server using a wireless transmitter via a wireless carrier. The personal data may then be posted on the subscriber's web site.

Figure 7 is a flow diagram of one embodiment for posting personal data of a subscriber on a web site. Referring to **Figure 7**, at processing block 704, web server 160 receives personal data of subscribers. In one embodiment, the personal data may be received from a plurality of personal data capture devices. The personal data may comprise physical data and biometrical parameters of each subscriber. The personal data may be stored in a repository of personal data which resides either directly on web server 160 or on a separate computer accessible by web server 160.

In one embodiment, the personal data of the subscriber is stored in the repository of personal data only if the subscriber maintains an account registered with web server 160. The account may be registered at any time before or simultaneously with first transmission of subscriber's personal data. At the time of creating the account, the subscriber may be required to provide a password or a code to prevent access to the personal data by anyone other than the subscriber. In one embodiment, the account information may be stored together with the personal data in the repository of the personal data. Alternatively, the account information may be stored in a separate database or file.

At processing block 706, the personal data is processed to create feedback information. Depending on the services selected by the subscriber, various feedback information may be created in response to the subscriber's personal data. In one

embodiment, a fitness instructor, an athletic trainer, a diet or nutrition specialist, a physician, or any other fitness or health specialist may be able to access the subscriber's personal data. One or more fitness or health specialists may analyze the personal data and create the feedback information. In alternate embodiments, the personal data or its portion may be analyzed by a software program which may either create the feedback information entirely or assist fitness or health specialists in creating the feedback information. The feedback information may be stored either in the repository of personal data or in a separate database residing on web server 160 or on a different computer accessible by web server 160.

At processing block 708, the feedback information is posted on a web site. As described above, the web site may be a personal web site of the subscriber or a company web site that can be accessed by all subscribers. In one embodiment, the personal data may be posted on the web site in various forms such as graphs, tables and map overlays. In addition, the subscriber's personal data may be compared with personal data of other subscribers or with this subscriber's history data. In one embodiment, when the personal web site is used, the web site may be specifically created as a part of services provided to the subscriber. Alternatively, the subscriber's existing web site may be used for posting the feedback information and the personal data of the subscriber. In yet another embodiment, the feedback information and personal data may be posted on a company web site known to all subscribers. In either embodiment, access to the feedback information and personal

data is protected either by a password or other means for maintaining confidentiality of personal information.

Several variations in the implementation of the method and system for transmitting data over a network using a docking device have been described. The specific arrangements and methods described here are illustrative of the principles of this invention. Numerous modifications in form and detail may be made by those skilled in the art without departing from the true spirit and scope of the invention. Although this invention has been shown in relation to a particular embodiment, it should not be considered so limited. Rather it is limited only by the appended claims.